



RUGGED CONNECTIVITY

ADVANCED DIAGNOSTICS & PROTOCOLS SPECIFICALLY DEVELOPED TO SUPPORT ACCESS FOR POWERSPORTS AND MARINE ENVIRONMENTS

DEFY DIAGNOSTICS

TEXA TXB2

Support repair technicians with essential diagnostic operations, including error reading and clearing, display of engineering parameters and status of control unit, activations, adjustments and configurations of the vehicle devices, deactivation of the warning lights, configuration of the control units, fuel trim and injection timing.



LED DISPLAY

Optimize Data Download Usability With New RGB LED Confirmation

DYNAMIC TEST

Rugged Design For Safe Parameter Recording Session While Moving

POWERFUL

Faster Processor With Latest Protocols For Precise Recording Of Data From Control Units

COVERAGE

Integrated 16-Pin Connector Latest Generation Bluetooth New USB C Data Download



Blink Codes / K, L, FD CAN
11898-2 CAN
ISO 11898-3

CAN SAE J2411
SAE J1850 SAE
J1708 / RS232

12V and 24V Vehicle
Battery Operate Band 2402
- 2480 MHz E Switch
2-way, 13 Independent



Cortex M7 550 MHz
Processor 1MB Flash /
256 MBit SRAM 8 GByte
eMMC Memory



16 Pin CPC
Connector Wireless
Bluetooth 5.0 High
Speed 2.0 USB C

25 Goldsmith St. #1006
Greenville SC 29609

WWW.DEFYDIAGNOSTICS.COM

MADE IN ITALY / OEM PARTNER



TEXA USA
TECH SUPPORT
855-200-8392